



ELESA original design CFTX.



Form SH

Form EH



Bohrungen für Senkschraube DIN 7991

Bohrungen für Zylinderschrauben DIN 912 Sechskantschraube ISO 4014



1

2

3

l ₁		l ₂		d ₁		d ₂	h ₁	h ₂	h ₃	h ₄ -0,5	h ₅	l ₃	m ₁ ±0,25	m ₂ ±0,25	sw
Nennmaß	Istmaß	Nennmaß	Istmaß												
40	38,5	40	39,5	4,5	3	13	9	4,5	4	18	16,5	25	25	7	
49	49	49	49,5	5,5	4	16,5	11,5	5	6	23	21	31	30,5	8,5	
49	49	49	49,5	6,5*	4	16,5	11,5	-	6	23	21	31	30,5	10	
65	64	65	65	6,5	5	21,5	15	9	7,5	30	27,5	40	40	10	

* nur in Form EH lieferbar

Ausführung

- Kunststoff (Polyamid PA)
 - schwarz, matt
 - temperaturbeständig bis 80 °C
- Stift
 - Kunststoff (Polyacetal POM)
- *Kunststoff-Eigenschaften* → Seite 1876
- *Angaben zur Belastbarkeit* → Seite 1851
- **RoHS-konform**

Hinweis

- siehe auch...
- *Zusammenstellung der Scharniere-Bauarten* → Seite 1152 ff.

Bestellbeispiel

1	l ₁
2	l ₂
3	d ₁
4	Form

GN 151.5-49-49-5,5-SH

3.1
3.2
3.3
3.4
3.5
3.6
3.7
3.8
3.9

