



4 Form (Fußteller)

A1 Stahl, verzinkt
Gummi eingelegt, schwarz

1		2		3		3						h ₁	l ₈	l ₉
d ₁	d ₂	Ausführung S / SK		Ausführung U / UK		Ausführung X								
50	M 8	40	50	63	-	-	-	-	-	-	40	18	25	45
50	M 10	50	60	80	100	-	-	-	-	-	43	18	25	45
50	M 12	60	80	100	125	-	-	-	-	-	47	18	25	45
50	M 16	-	-	-	-	75	100	125	150	200	52	18	25	45
60	M 8	40	50	63	-	-	-	-	-	-	41	19	25	50
60	M 10	50	60	80	100	-	-	-	-	-	44	19	25	50
60	M 12	60	80	100	125	-	-	-	-	-	48	19	25	50
60	M 16	-	-	-	-	75	100	125	150	200	53	19	25	50
80	M 8	40	50	63	-	-	-	-	-	-	42	20	30	70
80	M 10	50	60	80	100	-	-	-	-	-	45	20	30	70
80	M 12	60	80	100	125	-	-	-	-	-	49	20	30	70
80	M 16	-	-	-	-	75	100	125	150	200	54	20	30	70
80	M 20	-	-	-	-	75	100	125	150	200	62	20	30	70
80	M 24	-	-	-	-	100	125	150	200	-	-	20	30	70
100	M 8	40	50	63	-	-	-	-	-	-	43	21	30	80
100	M 10	50	60	80	100	-	-	-	-	-	46	21	30	80
100	M 12	60	80	100	125	-	-	-	-	-	50	21	30	80
100	M 16	-	-	-	-	75	100	125	150	200	55	21	30	80
100	M 20	-	-	-	-	75	100	125	150	200	63	21	30	80
100	M 24	-	-	-	-	100	125	150	200	-	-	21	30	80

Ausführung

- Fußteller / Lasche, Stahlblech
Stahl, verzinkt, blau passiviert
- Sechskantmutter ISO 4032
Stahl, verzinkt, blau passiviert
- Elastomer-Eigenschaften
→ Seite 1876
- Verstellspindel
Stahl verzinkt, blau passiviert
- Gummiauflage eingelegt
schwarz, Perbunan® (NBR)
80±5 Shore A
- Angaben zur Belastbarkeit
→ Seite 1864
- RoHS-konform

Ausführung - Spindelvarianten

<p>S ohne Mutter SK mit Mutter</p>	<p>U ohne Mutter UK mit Mutter</p>	<p>X mit Innengewinde</p>
<p>Außensechskant unten M 8, M 10, M 12</p>	<p>Innensechskant oben Schlüsselfläche unten M 16, M 20, M 24</p>	<p>Außensechskant Innengewinde M 8, M 10, M 12, M 16, M 20</p>

d ₁	d ₂	h ₃	h ₄	sw ₁	sw ₂	sw ₃	sw ₇	t
50	M 8	26	-	17	-	-	14	8
50	M 10	26	-	17	-	-	14	10
50	M 12	26	-	17	-	-	17	12
50	M 16	-	32	-	12	8	22	16
60	M 8	27	-	17	-	-	14	8
60	M 10	27	-	17	-	-	14	10
60	M 12	27	-	17	-	-	17	12
60	M 16	-	33	-	12	8	22	16
80	M 8	28	-	17	-	-	14	8
80	M 10	28	-	17	-	-	14	10
80	M 12	28	-	17	-	-	17	12
80	M 16	-	34	-	12	8	22	16
80	M 20	-	35	-	15	10	27	20
80	M 24	-	38	-	19	12	-	-
100	M 8	29	-	17	-	-	14	8
100	M 10	29	-	17	-	-	14	10
100	M 12	29	-	17	-	-	17	12
100	M 16	-	35	-	12	8	22	16
100	M 20	-	36	-	15	10	27	20
100	M 24	-	39	-	19	12	-	-

Hinweis

Stellfüße GN 32 werden montiert geliefert; sie sind nicht demontierbar.

siehe auch...

- *Edelstahl-Stellfüße GN 33 (mit Befestigungslasche)*
→ Seite 1294
- *Stellfüße GN 30 (Stahl, verzinkt, ohne Befestigungslasche)*
→ Seite 1288

Bestellbeispiel		1	d ₁
		2	d ₂
		3	l ₁ (l ₇)
		4	Form (Fußteller)
		5	Spindelvariante