



No.	d ₁ Ø Handwheel GN 321 GN 322 GN 323	d ₂ H7 Bore with keyway		d ₃	d ₄ max. see page 168	d ₅ Minimum-Ø of handwheel hub	d ₆ -0,03 Bore-Ø of hub d ₆ H7	l ₁	l ₂ ±0,1 Length of handwheel hub	l ₃	t	w min. see page 168
1	125	K 12	-	28	17	29	25	28,5	18	5	26	4
1	140	K 12	-	28	17	29	25	28,5	19	5	26	4
2	140	K 14	K 16	32	21	33	29	32,5	19	6	30	4
2	160	K 14	K 16	32	21	33	29	32,5	20	6	30	4
3	200	K 18	K 20	38	26	39	35	36,5	24	6	36	4
4	250	K 22	-	45	30	46	41	47,5	28	12	42	4

Specification

- Steel
nitrided
- Bearing surface ground resp.
PTFE-coated
- Keyway P9 DIN 6885 Page 2 → Page 1125
- ISO-Fundamental Tolerances → Page 1132
- RoHS compliant

Information

The PTFE-coated surfaces of the coupling attachments GN 000.4 provide minimal friction between bearing surfaces even when lubrication is being neglected.

An oil-hole is provided which in the completely assembled safety handwheel connects with the wheel hub.

see also...

- More information to safety handwheels → Page 166

How to order

GN000.4-2-K14

1 No.

2 Keyway d₂