



ROSTFREI
Inox
Stainless
Steel

Length $l \pm 3$	d_1	d_2	Static load in N \approx		suitable for ball lock pins and locking pins with axial lock
			with key ring	without key ring	
200	14 *	1	50	180	* GN 113.1, GN 113.3, GN 113.4 GN 113.7, GN 113.8, GN 214.2, GN 214.3, GN 214.6 for pins $\varnothing 5, \varnothing 6, \varnothing 8$ and * GN 113.5, GN 113.6, GN 114.2 GN 114.3, GN 114.6, GN 124.1 GN 124.2 ** GN 113.1, GN 113.3, GN 113.4 GN 113.7, GN 113.8, GN 214.2, GN 214.3, GN 214.6 for pins $\varnothing 10, \varnothing 12, \varnothing 16, \varnothing 20$
200	18 **	1,3	90	180	
200	24	1,5	100	180	
200	30	1,8	120	180	
320	14 *	1	50	180	
320	18 **	1,3	90	180	
320	24	1,5	100	180	
320	30	1,8	120	180	
500	14 *	1	50	180	
500	18 **	1,3	90	180	
500	24	1,5	100	180	
500	30	1,8	120	180	
1000	14 *	1	50	180	
1000	18 **	1,3	90	180	
1000	24	1,5	100	180	
1000	30	1,8	120	180	

Specification

- **GN 111**
Ball chain
Brass, nickel plated
- **GN 111.5**
Ball chain
Stainless Steel AISI 304
- Key ring
Stainless Steel AISI 301
- *Stainless Steel characteristics* → Page 1489
- **RoHS compliant**

Accessory

- Single key rings are supplied with code no. GN 111.3-d₁.

Information

Ball chains GN 111 / GN 111.5 are mainly used in connection with ball lock pins and locking pins with axial lock.

The key rings are supplied unmounted. Both rings have the same $\varnothing d_1$.

The load values given in the above table at shear stress are theoretically obtained and indicative only.

They are non-binding recommended values and rule out any liability.

How to order (Brass)	1	Length l
	2	d_1

GN 111-320-24

How to order (Stainless Steel)	1	Length l
	2	d_1

GN 111.5-200-14