



**1 Type**


- Operation
- RG** with knurled knob in plastic GN 7336
  - KG** with wing knob in plastic
  - HG** with lever in plastic
  - SG** with St. Steel-Star knob
  - KGN** with St. Steel-Wing knob
  - HGN** with St. Steel-Lever




Type KGN




Type HGN



Type RG



Type KG



Type HG

**2**

Latch distance **A**

6	10	14	18	20	22	24	26	28	30	34	38	40	50
---	----	----	----	----	----	----	----	----	----	----	----	----	----

**Specification**

- Lock housing  
Stainless Steel  
AISI 303
- Latch  
Stainless Steel AISI 304
- Star knobs (Type SG)  
Stainless Steel AISI 304  
- Sheet metal, drawn  
- Hub, welded
- Operating handles (Type KGN, HGN)  
Stainless Steel AISI CF-8
- Operating handles (Type RG, KG, HG)  
Plastic (Polyamide PA)  
black, matte
- Protection class IP 65
- *Stainless Steel characteristics* → Page 1489
- **RoHS compliant**

**3**

**Information**

Latches GN 115 lock by a turning operation limited to 90° which moves the locking behind the door frame. The bevels of the latch ease the closing of the door.

Latches with different cranks cover a latch distance A from 6 to 50 mm.

The operating bolt is fitted with an O-ring for sealing.

Stainless Steel-Latches GN 115 are supplied with loosely enclosed locking.

see also...

- *Construction and assembly instructions* → Page 897
- *List of latch types* → Page 892 ff.
- *Stainless Steel-Latches GN 115 (lockable)* → Page 902
- *IP-Protection classes* → Page 1482

How to order

**GN 115-SG-18-NI**

<b>1</b>	<b>Type</b>
<b>2</b>	<b>Latch distance A</b>
<b>3</b>	<b>Material</b>