



Inch sizes available

4 Type

- D** straight lever
- E** angled lever

1 2 3

d_1	d_2 Thread	l_1								d_3	d_4	d_5	h_1	h_2	h_3	$h_4 \approx$	h_5 Stroke	l_2
32	M 8	12	16	20	25	32	40	50	63	13,5	8	20	20,5	1,5	12,5	36	4	100
32	M 10	20	25	32	40	50	63	80	-	13,5	8	20	20,5	1,5	12,5	36	4	100
36	M 10	16	20	25	32	40	50	63	80	16	10	25	24,5	2	15	45	4,5	120
36	M 12	25	32	40	50	63	80	-	-	16	10	25	24,5	2	15	45	4,5	120
40	M 12	25	32	40	50	63	80	-	-	19	12	30	26,5	2	16	50	4,5	130
45	M 16	32	40	50	63	80	-	-	-	23	12	32	31,5	2	20	60	5	145

Specification

- Steel blackened
Threaded stud
Tensile strength class 5
- Plane surface with natural colored, anodized Aluminum-disc
- Ball knobs DIN 319
Plastic, Duroplast
black, shiny finish
- RoHS compliant

Information

The overall height of flat tension levers GN 125 is reduced to a minimum. As all other adjustable levers, they are ideal whenever parts have to be clamped in a confined space, or a particular lever position is required. The threaded insert is connected with the hub via serrations which can be disengaged.

Pulling the lever, disengages the serrations and the lever can be swivelled to the ideal clamping position. On releasing the lever it will automatically re-engage.

see also...

- Adjustable Stainless Steel-Flat tension levers GN 125.5 → Page 355
- Adjustable flat tension levers GN 126 (Threaded stud, steel) → Page XYZ

How to order

1 2 3 4
GN 125-32-M8-40-E

- 1 d_1
- 2 d_2
- 3 l_1
- 4 Type

