




Type A

Type B

Type C



4 Type

- A** without bores
(only in Stainless Steel NI)
- B** with through-holes
- C** with countersunk holes

2

3

l_1 on one side elongated	on both sides elongated	l_2	d_1	d_2	d_3	d_4	m_1	m_2	m_4	m_5	s
45	-	30	3	3,2	4	6,4	33	18	9	24	1,5
-	60	30	3	3,2	4	6,4	48	18	9	24	1,5
60	-	40	4	4,2	5	8,3	45	25	12,5	32,5	2
-	80	40	4	4,2	5	8,3	65	25	12,5	32,5	2
75	-	50	6	5,2	5	8,3	55	30	15	40	2
-	100	50	6	5,2	5	8,3	80	30	15	40	2
90	-	60	6	5,2	5	8,3	66	36	18	48	2
-	120	60	6	5,2	5	8,3	96	36	18	48	2

Specification

- Steel **ST**
 - only type B and C
 - zinc plated, blue passivated
- Stainless Steel AISI 304 **NI**
 - all types
- Pin
 - Stainless Steel AISI 304
 - riveted
- *Stainless Steel characteristics* → Page 1489
- *Load rating information* → Page 1459
- **RoHS compliant**

1

Information

GN 136 sheet metal hinges are available in many different versions and are suitable for light to medium-duty applications.

Type A can be fixed in place by welding or by using holes made by the customer.

see also...

- *List of hinge types* → Page 956 ff.
- *Sheet metal hinges GN 136 (square or vertically elongated)*

→ Page 965

How to order

GN 136-ST-60-40-B

- 1** Material
- 2** l_1
- 3** l_2
- 4** Type