



ELESA original design CFE.




Swivelling range

**3 Type**


- A** 2x2 threaded blind bores
- B** 2x2 bores for socket head cap screws
- C** 2x2 threaded studs
- D** 2x threaded blind bores / 2x threaded studs
- E** 2x threaded blind bores / 2x bores for socket head cap screws
- F** 2x threaded studs / 2x bores for socket head cap screws




Type A



Type B




Type C



Type D



Type E



Type F



1		2		d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	h <sub>1</sub>	h <sub>2</sub>	l <sub>3</sub>	l <sub>4</sub>	l <sub>5</sub>	m <sub>1</sub> ±0,3	m <sub>2</sub> ±0,3	r	t
Nominal dimension	Actual dimension	Nominal dimension	Actual dimension												
45	45,5	30	30,5	M 3	3,3	2,5	12,5	9,5	15	12	4	30	15	5	4
58	59	40	40,5	M 4	4,3	4	16,5	12,5	20	18	6	41	20	6	5,5
70	70	48	48	M 5	5,5	5	20	15	24	17	8	47	24	7	6,5
97	97	66	66	M 6	6,5	6	27	21	33	16	10	63,5	33	8	9

**Specification**

- Plastic (Polyamide PA)
  - black, matte
  - temperature resistant up to 80 °C
- Pin
  - Stainless Steel
  - German Material No. 1.4305
- Threaded bushings
  - Brass, nickel plated
- Threaded studs
  - Brass, nickel plated
- Plastic characteristics → Page 1483
- Stainless Steel characteristics → Page 1489
- Load rating information → Page xx
- RoHS compliant

How to order

**GN 155-58-40-F**

1	l <sub>1</sub>
2	l <sub>2</sub>
3	Type