



ELESA original design RDB

3 Form

- B** with drilling in the center, with two countersunk holes for cap screws
- D** with drilling in the center, with two hexagon nut for screwing
- BC** with drilling in the center, with two countersunk holes for cap screws, with a guide
- DC** with drilling in the center, with two hexagon nut for screwing, with a guide

1 2

d ₁	z Number of teeth	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	d ₈	h ₁	h ₂	h ₃	h ₄ (2 x h ₂)	m	sw	w min. Stroke
32	60	23,5	6,3	5	4	M 4	5	35,5	9,5	9	8,2	18	18	7	1,2
40	60	30	8,3	6	5	M 5	6	43,5	12	11,4	10,5	22,8	23	8	1,3

Specification

- Plastic
Technopolymer (Polyamide PA)
- glass fibre reinforced
- temperature resistant up to 80 °C
- black, matt
- Hexagon nuts
Stainless Steel AISI 304
- Plastic characteristics
→ Main Catalogue Page 1141
- RoHS compliant

Accessory

- Thrust springs GN 187.2

Information

With the aid of serrated locking plates GN 189 standard components can be interlocked and firmly set at a defined angle.
Together with the GN 187.2 compression spring, they ensure that the teeth disengage when loosened.

see also...

- Serrated locking plates (Sintered Steel / Stainless Steel) GN 187.4
→ Main Catalogue Page 554

How to order

GN 189-32-60-B

1	d ₁
2	z
3	Type