



2 Bore code

- B** without keyway
- K** with keyway
- V** with square

4 Type

- A** without handle
- D** with revolving handle (only available for GN 227.2)

1

3

3

d ₁	d ₂ H9 Bore	s H11 Square	b	d ₃	l ₁	l ₂ ≈	l ₃	r	Ø Handle	No. of spokes	Thickness of pressed Stainless Steel
160	12	V 12	22	30	20	39	83	68	26	4	2
200	14	V 14	22	40	24	44	83	88	26	4	2,5
250	17	V 17	30	45	28	52	93	108	28	5	3
315	19	V 19	36	55	33	64	93	138	28	5	3
400	24	V 24	43	65	38	81	93	178	28	5	3

Specification

GN 227.2

- Stainless Steel A2
- AISI 304
- matt shot-blasted
- Wheel body, pressed Stainless Steel
- Hub welded

Revolving handle similar to GN 598.1

- Plastic, Duroplast black, shiny
- Spindle Stainless Steel AISI 303

GN 227.4

- Stainless Steel A4
- AISI 316L
- matt shot-blasted
- Wheel body, pressed Stainless Steel
- Hub welded

- Keyway P9 DIN 6885 → Page 1420
- Square DIN 79 → Page 1424
- Cross holes GN 110 → Page 1422
- ISO-Fundamental tolerances → Page 1479
- Stainless Steel characteristics → Page 1489
- RoHS compliant

Information

The hub lengths of the pressed Stainless Steel-Handwheels GN 227.2 / GN 227.4 conform to DIN 950.

Stainless Steel-Handwheels GN 227.2 / GN 227.4 are renowned for their high mechanical strength. They are not affected by shock and knocks.

Stainless Steel-Handwheels GN 227.4 (A4 quality) are only available in type A (without handle).

see also...

- Stainless Steel-Countersunk washers GN 184.5 (for axial fixing) → Page 814
- Stainless Steel-Handwheels GN 950.6 → Page 182
- Stainless Steel-Handwheels GN 949 → Page 183

How to order (AISI 304 / A2)

1 2 3 4
GN 227.2-200-B14-D

1	d ₁
2	Bore code
3	d ₂ (s)
4	Type

How to order (AISI 316L / A4)

1 2 3 4
GN 227.4-160-V12-A

1	d ₁
2	Bore code
3	s (d ₂)
4	Type