



**4 Sensitivity**

- 6 Angle minutes, bubble move by 2 mm
- 50 Angle minutes, bubble move by 2 mm

**5 Identification no.**

- 1 Viewing window top
- 2 Viewing window top - front
- 3 Viewing window top - front - back

**2**

$l_1$	$b$	$d$	$h_1$	$h_2$	$l_2$	$m$
57	12	4,5	13	1	37	45

**Specification**

- Housing brass plastic coated, textured finish black, RAL 9005 ● **MSW**  
silver, RAL 9006 ● **MSR**
- Spirit level element Glass plastic body Filling green-transparent **G**
- Casting compound mineral-based
- **RoHS compliant**

**On request**

- Filling, colorless-transparent
- Other sensitivities
- Other colors

**Information**

Screw-on levels GN 2282 are used to check the horizontal position of jigs, machines, devices, appliances and instruments.

The spirit levels are aligned in relation to the finished reference surface so that the bubble is centered in the middle of the marking lines once the horizontal position of the contact surface in the longitudinal direction is reached.

see also...

- *General information on bull's eye levels and screw-on levels* → Page 243

**How to order**

<b>1</b>	<b>Material / Finish</b>
<b>2</b>	$l_1$
<b>3</b>	<b>Filling</b>
<b>4</b>	<b>Sensitivity</b>
<b>5</b>	<b>Identification no.</b>

**GN 2282-MSR-57-G-50-3**