



2 Type

- A** with male thread
- B** with female thread

1

d_1		d_2	d_3	$e \approx$	k_1	k_2	k_3	$l_1 \approx$	l_2	l_3 min. Type A	Type B	l_4	A/F	x max. shaft off-set	max. pull- /push load in kN
M 6	-	42	5,5	11	7	14	28	30,5	11	11	11	14	10	0,6	2,5
M 8	-	48	6,5	14,5	8	16	32	35,5	13	13,5	13,5	17	13	0,7	4,5
M 10	M 10 x 1,25	50	6,5	19	9	17	34	43	16	16	15	20	17	0,7	6,5
M 12	M 12 x 1,25	55	6,5	21	10	19	38	53	20,5	21	17,5	25	19	0,8	10
M 16	M 16 x 1,5	65	9	27	12,5	22,5	45	64	23	25	22	30	24	1	18
M 20	M 20 x 1,5	80	11	34	17	28	56	74	26	29	25	35	30	1	30

Specification

- Steel
- tempered
- phosphated
- **RoHS compliant**

Information

Quick-fit couplings GN 240.1 have been designed for the purpose of compensating in radial shaft-off-set x. A typical application is the axial link to a piston rod of a cylinder operating any type of fixture or system.

The coupling is **not** designed for the transfer of torque.

see also...

- Quick-fit couplings GN 240
(with radial off-set compensation) → Page 1171

How to order

GN 240.1-M12x1,25-B

1 d_1

2 Type