





Type OZ
without centring step
(smooth)




Type MZ
with centring step

Type AV
with male serration



Type IV
with female serration



- 2 Type**
- OZ** without centring step (smooth)
- MZ** with centring step
- AV** with male serration
- IV** with female serration
- 3 Identification no.**
- 2** with Stainless Steel-Clamping screw DIN 912

d ₁		b	d ₂	d ₃	d ₄	d ₅	k	Length l	m	s	Clamping kit for d ₃
Bore B without slide bushing	Bore G with slide bushing	Swivel width		Clamping thread		Mounting screw on the follower					
B 30	G 30	40	8,5	M 8	M 8	M 4	40	95	43	13	GN 911-M 8-32
B 40	G 40	65	10,5	M 10	M 10	M 5	65	148	70	17	GN 911-M10-55
B 50	G 50	65	10,5	M 10	M 10	M 6	65	148	70	17	GN 911-M10-55

Specification

- Aluminum plastic coated black, RAL 9005, textured finish **● SW**
- Guide bore mechanically machined
- Slide bushing Polyamide
- Socket cap screws DIN 912 Stainless Steel AISI 304
- Hexagon nuts DIN 985 Stainless Steel AISI 304
- *Stainless Steel characteristics* → Page 1489
- **RoHS compliant**

Accessory

- Clamping kits GN 911 → Page 1242

Information

GN 274.1 swivel clamp linear actuator connectors are normally supplied **mounted** only in connection with a linear actuator and for function control.

By means of the clamping screw on the guide bore d₁ the movement can either be set or the linear actuator connector can be clamped (after setting of final adjustment).

The standard version of the clamping screw is a socket cap screw with hexagonal socket DIN 912. It can be replaced by a clamping kit GN 911 (article code see table of dimensions).

see also...

- *Linear actuators GN 291* → Page 1326
- *Linear actuators GN 292* → Page 1328
- *Linear actuators GN 293* → Page 1329

How to order

1	d ₁
2	Type
3	Identification no.
4	Finish

GN 274.1-B30-OZ-2-SW

3.1
3.2
3.3
3.4
3.5
3.6
3.7
3.8
3.9