



3 Type

- S** stepless adjustment
- T** adjustment by 15°-division (serration)

4 Identification no.

- 2** with 3 Stainless Steel-Clamping screws DIN 912

1 2

d ₁ Bore B	d ₂ Bore B	b Swivel width	d ₃ Clamping thread	d ₄ Clamping thread	k ₁	k ₂	l ₁	l ₂	l ₃	m ₁	m ₂	Clamping kit	
												for d ₃	for d ₄
B 20	B 20	40	M 8	M 8	42,5	40	147	52	40	43	72	GN 911-M 8-32	GN 911-M 8-35
B 25	B 25	40	M 8	M 8	42,5	40	147	52	40	43	72	GN 911-M 8-32	GN 911-M 8-35
B 30	B 30	40	M 8	M 8	42,5	40	147	52	40	43	72	GN 911-M 8-32	GN 911-M 8-35
B 40	B 40	65	M 10	M 10	74	65	230	77,5	65	70	115	GN 911-M10-55	GN 911-M10-63
B 42	B 42	65	M 10	M 10	74	65	230	77,5	65	70	115	GN 911-M10-55	GN 911-M10-63
B 45	B 45	65	M 10	M 10	74	65	230	77,5	65	70	115	GN 911-M10-55	GN 911-M10-63
B 48	B 48	65	M 10	M 10	74	65	230	77,5	65	70	115	GN 911-M10-55	GN 911-M10-63
B 50	B 50	65	M 10	M 10	74	65	230	77,5	65	70	115	GN 911-M10-55	GN 911-M10-63

Specification

- Aluminum
 - plastic coated
 - black, RAL 9005, textured finish ● **SW**
 - blank ○ **BL**
 - matt shot-blasted
- Clamping bores mechanically machined
- Socket cap screws DIN 912
Stainless Steel AISI 304
- Hexagon nuts DIN 985
Stainless Steel AISI 304
- *Stainless Steel characteristics* → Page 1489
- **RoHS compliant**

Accessory

- Clamping kits GN 911 → Page 1242

Information

GN 288 swivel clamp connector joints are an assembly of swivel clamp connectors GN 276 and GN 278.

For the type with stepless adjustment (Type S) swivel clamp connectors with a centring step are used. Within the identical swivel width “b”, all bores “d₁ / d₂” can be combined as required.

The clamping bores are mechanically machined and designed for construction tubes GN 990 or DIN 2391, DIN 2395 and DIN 2462 respectively.

The standard version of the clamping screws are socket cap screws with hexagonal socket DIN 912. They can be replaced by clamping kits GN 911 (see table of dimensions).

see also...

- *Construction tubes GN 990* → Page 1277

How to order

1	d ₁
2	d ₂
3	Type
4	Identification no.
5	Finish

GN 288-**1**B25-**2**B25-**3**S-**4**2-**5**BL

3.1
3.2
3.3
3.4
3.5
3.6
3.7
3.8
3.9

