



<sup>1</sup> l <sub>1</sub>	<sup>2</sup> d <sub>1</sub> Thread			<sup>3</sup> d <sub>2</sub> H7 Bore		d <sub>3</sub>	d <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub> Stroke	t min.
30	M 3	-	-	-	-	10	13	26,5	4	31	3,5	7
30	M 4	M 5	M 6	B 5	B 6	10	13	26,5	4	31	3,5	9
45	M 4	M 5	M 6	B 5	B 6	10	13	26,5	4	35	3,5	9
63	M 6	M 8	-	B 8	-	13,5	17,5	32,5	6,5	45	4	11
78	M 8	M 10	-	B 8	B 10	16	21	37,5	8	55	4	14

**Specification**

- Handle  
Zinc die casting
- plastic coated  
black, RAL 9005  
textured finish ● SW
- Push button  
Plastic  
black, RAL 9005  
orange, RAL 2004  
grey, RAL 7035 ● S  
● O  
● G
- Threaded bushing  
Steel, blackened
- Pin for push button  
Stainless Steel
- ISO-Fundamental tolerances → Page 1479
- RoHS compliant

**On request**

- Handle in colors of GN 300

**Information**

Adjustable hand levers GN 303 are ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

The push button is a design element that offers an easy disengagement. Its use is limited to applications where dismantling of the lever for installation is not required.

see also...

- Adjustable hand levers GN 303.1  
(with push button, bushing Stainless Steel) → Page 330

How to order	<sup>1</sup> l <sub>1</sub>
	<sup>2</sup> d <sub>1</sub> (d <sub>2</sub> )
<b>GN303-78-M10-SW-G</b>	<sup>3</sup> Handle color
	<sup>4</sup> Push button color