



4 Type

- C** with tapped hole, no bushing
- E** with tapped bushing

2 d_1	3 d_2 KU Type C Thread	KT Type C Thread	3 d_3 KU Type E Thread	KT Type E Thread	$d_4 \approx$	h	t_1 min.	t_2 min.				
12	M 4	-	-	-	6	11,2	6	-				
16	M 4	M 5	-	M 4	M 5	M 4**	-	-	8	15	6	6
20	M 5	M 6	-	M 5	M 6	M 5	-	M 5	12	18	7,5	7,5
25	M 5	M 6	M 8	M 6	M 8	M 6	M 8*	M 6	15	22,5	9	9
30	M 8	-	-	-	-	-	-	-	15	28	12	-
32	M 6	M 8	M 10	M 8	M 10	M 8	-	M 8	18	29	12	12
35	M 10	-	-	-	-	-	-	-	18	32,5	15	-
40	M 8	M 10	M 12	M 10	M 12	M 10	-	-	22	37	15	15
50	M 12	-	-	-	-	M 12	-	-	28	46	18	18

* This size is only available in black with bushing in steel. ** This size is only available in black with bushing in brass.

Specification

- Plastic **KU**
Duroplast (Phenolic PF)
- Flash removed and polished
- black (standard color)
- red **RT**, similar RAL 3003:
add RT on order code
Bushing (Type E)
- Steel, zinc plated (standard)
- Brass **MS**
ad MS on order code

- Plastic **KT**
Technopolymer (Polyamide PA)
- shock resistant
- black, matte finish (standard color)
- red **RT**, similar RAL 3000:
add RT on order code
Bushing (Type E)
Steel, zinc plated
- *Plastic characteristics* → Page 1483
- **RoHS-compliant**

Information

- see also...
• *Ball knobs, Press on type DIN 319* → Page 48

How to order		1 Material
1	2	d₁
2	3	d₂ (d₃)
3	4	Type
DIN 319-KU-25-M6-C		