



4 Type

- C with tapped hole, no bushing
- E with tapped bushing

d ₁	d ₂		KT		d ₃		d ₄ ≈	h	t ₁ min.	t ₂ min.
	KU Type C Thread		Type C Thread	Type C Thread	KU Type E Thread	KT Type E Thread				
10	M 3	-	-	-	-	-	5	9,3	6	-
12	M 4	-	-	-	-	-	6	11,2	6	-
16	M 4	M 5	-	M 4	M 5	M 4**	8	15	6	6
20	M 5	M 6	-	M 5	M 6	M 5	12	18	7,5	7,5
25	M 5	M 6	M 8	M 6	M 8	M 6	15	22,5	9	9
30	M 8	-	-	-	-	-	15	28	12	-
32	M 6	M 8	M 10	M 8	M 10	M 8	18	29	12	12
35	M 10	-	-	-	-	-	18	32,5	15	-
40	M 8	M 10	M 12	M 10	M 12	M 10	22	37	15	15
50	M 12	M 14	-	-	-	M 12	28	46	18	18

* This size is only available in black with bushing in steel. ** This size is only available in black with bushing in brass.

Specification

- Plastic **KU**
Duroplast (Phenolic PF)
- Flash removed and polished
- black (standard color)
- red **RT**, similar RAL 3003:
add RT on order code
Bushing (Type E)
- Steel, zinc plated (standard)
- Brass **MS**
ad MS on order code

- Plastic **KT**
Technopolymer (Polyamide PA)
- shock resistant
- black, matte finish (standard color)
- red **RT**, similar RAL 3000:
add RT on order code
Bushing (Type E)
Steel, zinc plated
- *Plastic characteristics* → Page 1483
- **RoHS compliant**

Information

- see also...
• *Ball knobs, Press on type DIN 319* → Page 48

How to order		1	Material
		2	d ₁
		3	d ₂ (d ₃)
		4	Type

DIN 319-KU-25-M6-C