



EDELSTAHL®
Rostfrei
Inox
Stainless
Steel

4 **Type (Base plate)**
B1 matt shot-blasted,
rubber inlaid, black

d ₁	d ₂	1					2					3					l ₇	A/F ₇	t									
		Version S / SK					Version T / TK und U / UK					Version V / VK								Version W								
50	M 8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	40	14	8						
50	M 10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	43	14	10						
50	M 12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	-	-	47	17	12						
50	M 16	-	-	-	-	75	100	125	150	200	-	-	-	-	-	-	-	-	-	52	22	16						
60	M 8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	41	14	8						
60	M 10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	44	14	10						
60	M 12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	-	-	48	17	12						
60	M 16	-	-	-	-	75	100	125	150	200	75	100	125	150	126	151	176	201	53	22	16							
80	M 8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	42	14	8						
80	M 10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	45	14	10						
80	M 12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	-	-	49	17	12						
80	M 16	-	-	-	-	75	100	125	150	200	75	100	125	150	127	152	177	202	54	22	16							
80	M 20	-	-	-	-	75	100	125	150	200	100	125	150	200	151	176	201	251	62	27	20							
80	M 24	-	-	-	-	100	125	150	200	-	100	150	200	-	176	226	276	-	-	-	-	-						
100	M 8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	43	14	8						
100	M 10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	46	14	10						
100	M 12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	-	-	50	17	12						
100	M 16	-	-	-	-	75	100	125	150	200	75	100	125	150	128	153	178	203	55	22	16							
100	M 20	-	-	-	-	75	100	125	150	200	100	125	150	200	152	177	202	252	63	27	20							
100	M 24	-	-	-	-	100	125	150	200	-	100	150	200	-	177	227	277	-	-	-	-	-						

Specification

- Base plate / lug, sheet metal
Stainless Steel AISI 304
- Threaded stem
Stainless Steel AISI 303
- Hexagon nut ISO 4032
Stainless Steel, AISI 304
- Rubber underlay, inlaid
black, Perbunan® (NBR)
80±5 Shore A
- Stainless Steel characteristics
→ Page 1489
- Elastomer characteristics
→ Page 1483
- RoHS compliant

Versions of threaded stem

<p>S without nut SK with nut</p>	<p>T without nut TK with nut</p>	<p>U without nut UK with nut</p>
<p>External hexagon at the bottom at d_2 M 8, M 10, M 12</p>	<p>Wrench flat at the bottom at d_2 M 16, M 20, M 24</p>	<p>Hexagon socket at the top Wrench flat at the bottom at d_2 M 16, M 20, M 24</p>
<p>V without nut VK with nut</p>	<p>W with adjustable sleeve</p>	<p>X with female thread</p>
<p>External hexagon at the top Wrench flat at the bottom at d_2 M 16, M 20, M 24</p>	<p>Covered thread and wrench flat at the bottom at d_2 M 16, M 20, M 24</p>	<p>External hexagon with female thread at d_2 M 8, M 10, M 12, M 16, M 20</p>

d_1	d_2	d_3	d_4	h_1	h_3	h_4	h_5	l_4	l_5	l_6	l_8	l_9	A/F ₁	A/F ₂	A/F ₃	A/F ₄	A/F ₅	A/F ₆		
50	M 8	M 10	M 12	-	13	18	26	-	-	-	-	25	45	17	-	-	-	-	-	
50	M 16	-	-	-	13	18	-	32	-	-	-	25	45	-	12	8	-	-	-	
60	M 8	M 10	M 12	-	13	19	27	-	-	-	-	25	50	17	-	-	-	-	-	
60	M 16	-	-	24	13	19	-	33	30	45	45	29	25	50	-	12	8	10	12	20
80	M 8	M 10	M 12	-	13	20	28	-	-	-	-	30	70	17	-	-	-	-	-	-
80	M 16	-	-	24	13	20	-	34	31	45	45	29	30	70	-	12	8	10	12	20
80	M 20	-	-	30	13	20	-	35	32	56	56	36	30	70	-	15	10	13	16	24
80	M 24	-	-	35	13	20	-	38	35	67	67	42	30	70	-	19	12	17	20	30
100	M 8	M 10	M 12	-	13	21	29	-	-	-	-	30	80	17	-	-	-	-	-	-
100	M 16	-	-	24	13	21	-	35	32	45	45	29	30	80	-	12	8	10	12	20
100	M 20	-	-	30	13	21	-	36	33	56	56	36	30	80	-	15	10	13	16	24
100	M 24	-	-	35	13	21	-	39	36	67	67	42	30	80	-	19	12	17	20	30

Information

Stainless Steel-Levelling feet GN 33 will be delivered mounted and are not removable.

see also...

- Levelling feet GN 32 (Steel, zinc plated) → Page 1048
- Stainless Steel-Levelling feet GN 31 (without lug) → Page 1046

- Load rating information → Page 1472

How to order

1	d_1
2	d_2
3	l_1 (l_2, l_3, l_7)
4	Type (Base plate)
5	Version (Stem)

GN33-60-M16-100-B1-V