



EDELSTAHL®
Rost
frei
Inox
Stainless
Steel

4 Type (Base plate)
B1 matt shot-blasted,
rubber inlaid, black

d ₁	d ₂	1					2					3					l ₇	A/F ₇	t		
		Version S / SK					Version T / TK und U / UK					Version V / VK								Version W	
50	M 8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	40	14	8	
50	M 10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	43	14	10	
50	M 12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	47	17	12	
50	M 16	-	-	-	-	75	100	125	150	200	-	-	-	-	-	-	-	52	22	16	
60	M 8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	41	14	8	
60	M 10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	44	14	10	
60	M 12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	48	17	12	
60	M 16	-	-	-	-	75	100	125	150	200	75	100	125	150	126	151	176	201	53	22	16
80	M 8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	42	14	8	
80	M 10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	45	14	10	
80	M 12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	49	17	12	
80	M 16	-	-	-	-	75	100	125	150	200	75	100	125	150	127	152	177	202	54	22	16
80	M 20	-	-	-	-	75	100	125	150	200	100	125	150	200	151	176	201	251	62	27	20
80	M 24	-	-	-	-	100	125	150	200	-	100	150	200	-	176	226	276	-	-	-	-
100	M 8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	43	14	8	
100	M 10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	46	14	10	
100	M 12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	50	17	12	
100	M 16	-	-	-	-	75	100	125	150	200	75	100	125	150	128	153	178	203	55	22	16
100	M 20	-	-	-	-	75	100	125	150	200	100	125	150	200	152	177	202	252	63	27	20
100	M 24	-	-	-	-	100	125	150	200	-	100	150	200	-	177	227	277	-	-	-	-

Specification

- Base plate / lug, sheet metal
Stainless Steel AISI 304
- Threaded stem
Stainless Steel AISI 303
- Hexagon nut ISO 4032
Stainless Steel, AISI 304
- Rubber underlay, inlaid
black, Perbunan® (NBR)
80±5 Shore A
- Stainless Steel characteristics
→ Page 1489
- Elastomer characteristics
→ Page 1483
- RoHS compliant

Versions of threaded stem

<p>S without nut SK with nut</p>	<p>T without nut TK with nut</p>	<p>U without nut UK with nut</p>
<p>External hexagon at the bottom M 8, M 10, M 12</p>	<p>Wrench flat at the bottom M 16, M 20, M 24, M 30 „not dipping“ version</p>	<p>Hexagon socket at the top Wrench flat at the bottom M 16, M 20, M 24</p>
<p>V without nut VK with nut</p>	<p>W with adjustable sleeve</p>	<p>X with female thread</p>
<p>External hexagon at the top Wrench flat at the bottom M 16, M 20, M 24</p>	<p>Wrench flat at the bottom M 16, M 20, M 24</p>	<p>External hexagon Female thread M 8, M 10, M 12, M 16, M 20</p>

d ₁	d ₂	d ₃	d ₄	h ₁	h ₃	h ₄	h ₅	l ₄	l ₅	l ₆	l ₈	l ₉	A/F ₁	A/F ₂	A/F ₃	A/F ₄	A/F ₅	A/F ₆
50	M 8 M 10 M 12	- 13	18	26	- -	- -	- -	- -	- -	- -	25	45	17	- -	- -	- -	- -	- -
50	M 16	- 13	18	- 32	- -	- -	- -	- -	- -	- -	25	45	- 12	8	- -	- -	- -	- -
60	M 8 M 10 M 12	- 13	19	27	- -	- -	- -	- -	- -	- -	25	50	17	- -	- -	- -	- -	- -
60	M 16	- 24 13	19	- 33	30	45	45	29	25	50	- 12	8	10	12	20	- -	- -	- -
80	M 8 M 10 M 12	- 13	20	28	- -	- -	- -	- -	- -	- -	30	70	17	- -	- -	- -	- -	- -
80	M 16	- 24 13	20	- 34	31	45	45	29	30	70	- 12	8	10	12	20	- -	- -	- -
80	M 20	- 30 13	20	- 35	32	56	56	36	30	70	- 15	10	13	16	24	- -	- -	- -
80	M 24	- 35 13	20	- 38	35	67	67	42	30	70	- 19	12	17	20	30	- -	- -	- -
100	M 8 M 10 M 12	- 13	21	29	- -	- -	- -	- -	- -	- -	30	80	17	- -	- -	- -	- -	- -
100	M 16	- 24 13	21	- 35	32	45	45	29	30	80	- 12	8	10	12	20	- -	- -	- -
100	M 20	- 30 13	21	- 36	33	56	56	36	30	80	- 15	10	13	16	24	- -	- -	- -
100	M 24	- 35 13	21	- 39	36	67	67	42	30	80	- 19	12	17	20	30	- -	- -	- -

Information

Stainless Steel-Levelling feet GN 33 will be delivered mounted and are not removable.

see also...

- Levelling feet GN 32 (Steel, zinc plated) → Page 1048
- Stainless Steel-Levelling feet GN 31 (without lug) → Page 1046

• Load rating information → Page 1472

How to order

1	d ₁
2	d ₂
3	l ₁ (l ₂ , l ₃ , l ₇)
4	Type (Base plate)
5	Version (Stem)

GN33-60-M16-100-B1-V