



3 Type

A Mounting from the back (threaded blind bore)

1

2

| d ₁ | Length l ±0,25 | | | | | d ₂ | b ₁ | b ₂ | h ₁ | h ₂ | t min. |
|----------------|----------------|-----|-----|-----|-----|----------------|----------------|----------------|----------------|----------------|--------|
| 28 | 242 | 292 | 392 | 492 | 592 | M 8 | 25 | 14 | 50 | 66 | 15 |

Specification

4

- Tube
Aluminum (wall thickness 1,5)
- Handle legs
Zinc die casting
plastic coated
- Cover
Plastic
- Tube / handle legs **● SW**
plastic coated
black, RAL 9005, textured finish
Cover
black, matt
- Tube **● ELS**
anodized, natural color
Handle legs
black, RAL 9005, textured finish
Cover
black, matt
- Tube **● ELG**
anodized, natural color
Handle legs
silver, RAL 9006, textured finish
Cover
light grey, matt
- Load rating information → Page 1451
- RoHS compliant

On request

- Special lengths

Information

The spacing of the attachment holes of the tubular handles GN 333.3 is adjustable.

Further handle legs can be added for very long tubular handles. Individual handle legs for tubular handles Ø 28 (type A) are available under GN 333.9 → Page 135.

Tubular handles GN 333.3 are supplied unassembled.

see also...

- Handle legs GN 333.9 (for tubular handles Ø 28) → Page 135
- Handle tubes GN 930 → Page 153

How to order

| | |
|----------|----------------|
| 1 | d ₁ |
| 2 | Length l |
| 3 | Type |
| 4 | Finish |

GN333.3-28-292-A-ELG

