



**3 Type**

**A** Mounting from the back (threaded blind bore)

**1**

**2**

d <sub>1</sub>	Length l ±0,25					d <sub>2</sub>	b <sub>1</sub>	b <sub>2</sub>	h <sub>1</sub>	h <sub>2</sub>	t min.
28	242	292	392	492	592	M 8	25	14	50	66	15

**Specification**

**4**

- Tube  
Aluminum (wall thickness 1,5)
- Handle legs  
Zinc die casting  
plastic coated
- Cover  
Plastic
- Tube / handle legs **● SW**  
plastic coated  
black, RAL 9005, textured finish  
Cover  
black, matte
- Tube **● ELS**  
anodized, natural color  
Handle legs  
black, RAL 9005, textured finish  
Cover  
black, matte
- Tube **● ELG**  
anodized, natural color  
Handle legs  
silver, RAL 9006, textured finish  
Cover  
light gray, matte
- Load rating information → Page 1451
- RoHS compliant

**On request**

- Special lengths

**Information**

The spacing of the attachment holes of the tubular handles GN 333.3 is adjustable.

Further handle legs can be added for very long tubular handles. Individual handle legs for tubular handles Ø 28 (type A) are available under GN 333.9 → Page 135.

Tubular handles GN 333.3 are supplied unassembled.

see also...

- Handle legs GN 333.9 (for tubular handles Ø 28) → Page 135
- Handle tubes GN 930 → Page 153

**How to order**

<b>1</b>	d <sub>1</sub>
<b>2</b>	Length l
<b>3</b>	Type
<b>4</b>	Finish

**GN333.3-28-292-A-ELG**

