



1.1

1.2

1.3

1.4

1

2

b	l <sub>1</sub> ±0,5	a	d	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	l <sub>2</sub>	l <sub>3</sub>	l <sub>4</sub>	l <sub>5</sub>
36	200	24	8,5	57	72	5	215	171	139	41
36	250	24	8,5	57	72	5	265	221	189	41
36	300	24	8,5	57	72	5	315	271	239	41
36	350	24	8,5	57	72	5	365	321	289	41
36	400	24	8,5	57	72	5	415	371	339	41
36	500	24	8,5	57	72	5	515	471	439	41
36	600	24	8,5	57	72	5	615	571	539	41
36	800	24	8,5	57	72	5	815	771	739	41

2.1

Specification

3

- Handle tube  
Aluminum
- Handle legs  
Zinc die casting  
plastic coated
- Tube ● SW  
plastic coated  
black, RAL 9005, textured finish  
Handle legs  
black, RAL 9005, textured finish
- Tube ● EL  
anodized, natural color  
Handle legs  
black, RAL 9005, textured finish
- Tube ● ES  
anodized, natural color  
Handle legs  
silver, RAL 9006, textured finish
- Cover  
Plastic, light gray
- Load rating information → Page 1451
- RoHS compliant

Information

Oval tubular handles GN 334.1 are highly stable.  
The handle tube can be mounted without any further machining, allowing **special lengths** to be realised easily.

see also...

- Product family Standard Parts for profile systems → Page 20
- Assembly sets for profile systems 30 / 40 GN 965 → Page 1428
- Assembly sets for profile systems 30 / 40 / 45 GN 968 → Page 1438

2.2

2.3

2.4

How to order

GN334.1-36-400-ES

1	b
2	l <sub>1</sub>
3	Finish

