



1		2		3					
b	d		$l_1 \pm 0,5$	a	h	$l_2$	$l_3$	$l_4$	t min.
36	M 6	M 8	200	24	57	236	164	290	15
36	M 6	M 8	250	24	57	286	214	340	15
36	M 6	M 8	300	24	57	336	264	390	15
36	M 6	M 8	400	24	57	436	364	490	15
36	M 6	M 8	500	24	57	536	464	590	15
36	M 6	M 8	600	24	57	636	564	690	15

**Specification**

- Handle tube  
Aluminum
- Handle legs / Cover cap  
plastic  
Technopolymer (Polyamide PA)  
- glass fiber reinforced  
- temperature resistant up to 100 °C
- Tube ● SW  
plastic coated  
black, RAL 9005, textured finish  
Handle legs / Cover cap  
black, matt
- Tube anodized, natural color ● ELS  
Handle legs / Cover cap  
black, matt
- Tube anodized, natural color ● ELG  
Handle legs / Cover cap  
light grey, matt
- Bushing  
Steel, zinc plated
- *Plastic characteristics* → Page 1483
- *Load rating information* → Page 1451
- **RoHS compliant**



**Information**

Characteristic for the design of the GN 366 oval handles: Tube and handle shank are made in the same elliptical profile.

see also...

- *Oval tubular handles GN 334 (Mounting from the back)* → Page 142

**How to order**

1	<b>b</b>
2	<b>d</b>
3	<b><math>l_1</math></b>
4	<b>Finish</b>

**GN366-36-M8-400-ELS**