



ROSTFREI
Inox
Stainless
Steel

d₁	l₁				d₂	d₃	d₄	d₅	d₆	h	k	l₂	l₃	l₄
M 6	25	35	45	15	24	12	14	4,5 ±0,03	16,5	9,5	5,1	3,6	7,6	
M 8	30	40	50	18	30	14	16	6,1 ±0,05	19,5	11	6,2	4,2	9,2	
M 8	30	40	50	21	30	14	16	6,1 ±0,05	19,5	11	6,2	5	10	
M 8	30	40	50	25	30	14	16	6,1 ±0,05	19,5	11	6,2	5,5	10,5	
M 8	30	40	50	32	30	14	16	6,1 ±0,05	19,5	11	6,2	6	11	
M 8	30	40	50	40	30	14	16	6,1 ±0,05	19,5	11	6,2	8	13	
M 10	35	45	55	21	36	16	18	7,8 ±0,03	22,5	12,5	7,3	4,3	10	
M 10	35	45	55	25	36	16	18	7,8 ±0,03	22,5	12,5	7,3	4,6	10,5	
M 10	35	45	55	32	36	16	18	7,8 ±0,03	22,5	12,5	7,3	5	11	
M 10	35	45	55	40	36	16	18	7,8 ±0,03	22,5	12,5	7,3	7	13	

Specification

- Knurled screw GN 421
Plastic, Technopolymer (Polyamide PA)
black, shiny finish
- Threaded stud
Stainless Steel AISI 303
- Thrust pad
Plastic
Technopolymer (Polyacetal POM)
- temperature resistant up to 80 °C
- black, matt
- *Stainless Steel characteristics* → Page 1489
- *Plastic characteristics* → Page 1483
- **RoHS compliant**

Information

Knurled screws GN 421.11 / GN 421.12 have a ball pin whose diameter is smaller than the core diameter of the thread.
The movable thrust pad is easily clipped on and taken off.
The thrust pads are supplied disassembled.

see also...

- *Star knobs GN 6336.12 (with movable thrust pad)* → Page 403
- *Knurled screws GN 421.11 / GN 421.12 with loss protection GN 111.7*
→ Page 1426

How to order (with ball pin)	1	d ₁
	2	l ₁
GN 421.11-M8-30		

How to order (with movable thrust pad)	1	d ₁
	2	l ₁
	3	d ₂
GN 421.12-M10-45-21		