





Range extended!



ELESA Original design MBT.-SOFT

SOFT



¹ d ₁	² d ₂ H9	² d ₃	³ Length l			d ₄	h ₁	h ₂	t min.
44	B 6	M 6	10	20	-	17	24	10	13
44	-	M 8	16	30	50	17	24	10	13
54	B 8	M 8	16	30	50	20	30	12,5	18
54	-	M 10	20	30	50	20	30	12,5	18

Specification

- Plastic
Technopolymer (Polypropylen PP)
- Rim Soft Elastomer (TPE)
70 Shore A
- temperature resistant up to 90 °C
- black, matt finish
- Softline lagging and plastic core chemically bonded
- Bush
Brass
- Threaded bolt
Steel zinc plated, blue passivated
- ISO-Fundamental tolerances → Page xx
- Elastomer characteristics → Page xx
- Plastic characteristics → Page xx
- RoHS compliant

Information

The Softline lagging on the contact surface of the knurled knob GN 4534 makes these knobs particularly „operator friendly“ and hence ergonomic. The soft and slip free surface makes it very contact friendly either for moist hands (perspiration), oily surfaces or even in high or low temperatures.

Besides its soft surface this knob has a large rim area which helps to distribute the operator’s contact grip and at the same time a higher torque can be reached.

Softline-Knurled knob ¹ ² GN4534-54-M10	1	d ₁
	2	d ₃ (d ₂)

Softline-Knurled knob with threaded bolt ¹ ² ³ GN4534-44-M8-16	1	d ₁
	2	d ₃
	3	Length l