



ROSTFREI®
Inox
Stainless
Steel

1 2

Steel												
d ₁	Length l								d ₂	d ₃	h	k
M 3	6	10	12	16	20	-	-	-	12	6	7,5	2,5
M 4	5	8	10	12	16	20	25	-	16	8	9,5	3,5
M 5	6	8	10	12	16	20	25	30	20	10	11,5	4
M 6	8	10	12	16	20	25	30	35	24	12	15	5
M 8	12	16	20	25	30	35	40	-	30	16	18	6
M 10	15	20	25	30	35	40	-	-	36	20	23	8

1 2

Stainless Steel												
d ₁	Length l								d ₂	d ₃	h	k
M 3	6	10	12	16	-	-	-	-	12	6	7,5	3
M 4	8	10	12	16	20	25	-	-	16	8	9,5	3,5
M 5	10	12	16	20	25	30	-	-	20	10	11,5	4
M 6	12	16	20	25	30	35	-	-	24	12	15	5
M 8	16	20	25	30	35	-	-	-	30	16	18	6

Specification

- Steel —
 - Tensile strength class 5.8
 - visible face fine turned
 - blackened
- Stainless Steel **NI**
 - AISI 303
 - matt shot-blasted
- *Stainless Steel characteristics* → Page 1489
- *Strength values of screws* → Page 1481
- **RoHS compliant**

Information

Knurled screws DIN 464 are machined from solid bar. Unlike in the official standard sheet, they are generally made with thread right up to the head and without recess groove at the end of the thread. The official standard sheet also provides for the sizes M1 / M1,2 / M1,6 / M2 and M2,5.

see also...

- *Stainless Steel-Knurled screws GN 535* → Page 452
- *Knurled screws DIN 464 with loss protection GN 111.7* → Page 1426

How to order (Steel)	1	d ₁
	2	Length l
DIN 464-M6-20		

How to order (Stainless Steel)	1	d ₁
	2	Length l
	3	Material
DIN 464-M6-20-NI		