



1

2

2

Length l	d <sub>1</sub> H7 Bore	s H11 Square	d <sub>2</sub>	d <sub>3</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub>	h <sub>5</sub> ≈	Ø Handle
80	B 10	V 10	23	29	20	4	26	4,3	43	16
100	B 12	V 12	26	34	24	5,5	30	4,2	57,5	18
125	B 14	V 14	28	36	31	10,5	37	4,2	76,5	24

## Specification

3

- Body  
Aluminum
  - plastic coated  
black, RAL 9005, textured finish ● SW
  - silver, RAL 9006, textured finish ● SR
  - hub machined
- Hub cover  
light gray
- Retractable handles GN 798.3
  - Plastic, Technopolymer  
black, matt finish
  - Retractable mechanism  
Steel, blackened
- Retractable handles GN 798.5
  - Plastic, Technopolymer  
black, matt finish
  - Retractable mechanism  
Stainless Steel
    - Axle parts AISI 303
    - Flat base  
Sintered Steel AISI 316
- Square DIN 79 → Page 1242
- Cross holes GN 110 → Page 1422
- ISO-Fundamental tolerances → Page 1479
- Stainless Steel characteristics → Page 1489
- RoHS compliant

## Information

The handpiece of the cranked handle GN 472.3 / GN 472.5 is locked in a tapered bore in the operating position.

For tilting, the handle must first be pulled out of the taper in axial direction.

A compression spring holds the handle in both end positions. When folded out, it automatically re-engages.

How to order (Retractable mechanism steel)

GN 472.3-100-V12-SR

1	Length l
2	s (d <sub>1</sub> )
3	Color

How to order (Retractable mechanism Stainless Steel)

GN 472.5-125-B14-SW

1	Length l
2	d <sub>1</sub> (s)
3	Color