



1 d_1 Bore B for shaft tol. h11	2 d_2			d_3 Clamping thread	k	m	l_1	l_2	l_3	s Square V	Clamping kits for d_3
B 8	M 5	-	-	M 4	14	-	25	13,5	7,5	-	GN 511-M4-14
B 10	M 5	M 6	M 8	M 5	16	-	30	17	8	8	GN 511-M5-16
B 12	M 5	M 6	M 8	M 5	16	-	32	17	9	10	GN 511-M5-16
B 15	M 6	M 8	-	M 6	20	14	40	20,5	12	12	GN 511-M6-20
B 16	M 6	M 8	-	M 6	20	14	40	20,5	11,5	-	GN 511-M6-20
B 20	M 8	M 10	-	M 6	25	17	45	21,5	12	16	GN 511-M6-25

Specification

- Aluminum
- matt, slide ground
- anodized, black

MT
ELS

- Socket cap screws DIN 912
Stainless Steel AISI 304
- Stainless Steel characteristics → Page 1489
- RoHS-compliant

Accessory

- Clamping kits GN 511 → Page 1260

Information

Clamp mountings GN 478 are primarily designed for mounting sensor holders GN 479 and retaining plates GN 479.1. They are fitted with a central thread and, with $d_1 = B15$ bore and higher, an additional bore template 4 x M4.

The standard clamping screw is a socket cap screw with hexagonal socket DIN 912. It can be replaced by a clamping kit GN 511 (article code see table of dimensions).

see also...

- Sensor holders GN 479 → Page 1262
- Retaining plates GN 479.1 → Page 1263
- Retaining rods / Retaining tubes GN 480.1 → Page 1276

How to order

GN 478-B16-M6-ELS

1	d_1
2	d_2
3	Finish