



ELESA Original design ME.

¹ l_1	² d_1 H7 Bore	d_2	b_1	b_2	h_1	h_2	$h_3 \approx$	l_2	t min.	\varnothing Handle
65	B 8	13	19	22	18	23	40	23	13	18
80	B 10	14	20	24	20	26	40	30	16	18
95	B 10	14	22	26	22	29	50	36	19	21
110	B 12	18	22	28	24	34	65	44	18	23
140	B 12	18	24	30	26	37	80	57	18	26

Specification

- Body
Plastic
Duroplast (Phenolic PF)
- reinforced
- temperature resistant up to 110 °C
- black, shiny finish
- Hub bushing
Steel, blackened
- Threaded bushing to accept the revolving handle
Brass
- Revolving handles GN 598
Plastic, Duroplast
black, shiny finish
- ISO-Fundamental Tolerances → Page XYZ
- RoHS-compliant

Information

Cranked handles GN 510 allow fine adjustment.
 These cranked handles are fitted to shaft with a cross pin. To simplify the installation there is a centred drilling on both sides.
see also...
 • Control handles GN 112.1 (Zinc die casting) → Page XYZ
 • Tri-ball handles GN 10 (Steel, turned) → Page XYZ

How to order	¹ l_1
	² d_1

GN 510-80-B10

1.1
1.2
1.3
1.4
1.5
1.6
1.7
1.8
1.9