



ELESA Original design I.H.N.

1

2

d_1	d_2 Bore B	d_3	d_4 Symbol- \emptyset	h	t
27	B 8	15	20	42	25
32	B 10	18	25	49	25

Specification

- Plastic
Technopolymer (Polyamide PA)
- temperature resistant up to 90 °C
- black, shiny finish
- transparent sight cap
with magnifying effect
- Positioning symbols on self adhesive foil
printed in silver-gray / black
- *ISO-Fundamental Tolerances* → Page 1479
- *Plastic characteristics* → Page 1483
- RoHS-compliant

Accessory

- Positioning symbols for tapered knobs
GN 517.1 are to be ordered separately.

Information

The tapered knobs GN 518 do not require a thread at the shaft. During mounting, easy blows with a soft hammer are sufficient to drive the knob into place, the shaft end should be slightly rounded or chamfered (30°). The knobs sit absolute vibration-tight.

The transparent sight glass allows symbols to be placed underneath.

Once the knob is mounted on the shaft, the symbol is placed into the recess of the separately supplied sight glass and driven home with a soft hammer.

The symbol is fully protected from dirt and liquid by the tight connection between the sight glass and the knob.

see also...

- *Softline-Mushroom shaped handles GN 718.1 (Press on type)*

How to order

GN518-32-B10

1 d_1

2 d_2