



ELESA Original design I.680 SOFT



¹ d ₁ +0,5	² d ₂	d ₃	l ₁	l ₂ min.	l ₃
24	M 8	20,5	65	30	7
24	M 10	20,5	65	40	7
26	M 8	21	80	40	7
26	M 10	21	80	55	7
26	M 12	21	80	55	7
28	M 10	22	90	56	7
28	M 12	22	90	58	10

Specification

- Plastic
Technopolymer (Polypropylene PP)
- Softline-coating
Elastomer (TPE) 70 Shore A
 - chemically bonded with the plastic core
 - with FDA admission
 - temperature resistant up to 80 °C
 - black, matte finish
- [Elastomer characteristics](#) → Page 1483
- [Plastic characteristics](#) → Page 1483
- **RoHS compliant**

Information

The softline coating of the cylindrical knobs GN 519.6 makes this knobs ergonomically and operator friendly.

The **soft, antislip** contact surface is very user friendly. It improves the contact between a damp (perspiration) or a dry hand, or oily surface, whether in a cold or hot environment.

see also...

- [Product family Softline](#) → Page 17
- [Cylindrical knobs GN 519 \(with thread\)](#) → Page 52
- [Cylindrical knobs GN 519.1 \(Press-on type\)](#) → Page 53

How to order	¹ d ₁
	² d ₂

GN 519.6-26-M10