



ELESA original design VD.FP



2 Bore code

- B** without keyway
- K** with keyway

4 Type

- A** without handle
- D** with revolving handle



d ₁		d ₂ H7		d ₃	d ₄	d ₅	d ₆	d ₇	b	l ₁ -0,5	l ₂ -0,5	l ₃	l ₄	r	Ø Handle
GN 520 Hub Steel	GN 520.6 Hub Stainless Steel	Bore													
50	-	10	-	16	16	-	25	26	12	8,5	18,5	22	28	19	14
63	-	10	-	20	20	-	31	28	13	10	23,5	28	40	24	18
80	-	10	12	20	16	28	43	30	14	10	28	31	40	32	18
100	100	10	12	24	20	35	54	39	15	12	36	40	50	41	21
125	125	12	14	32	24	44	70	46	15	15	38	44	65	53	23
150	150	14	16	32	24	44	70	48	18	15	38	48	65	64	23
175	-	16	18	40	31	55	90	56	19	15	43	53	80	75	26
200	200	18	20	40	31	55	90	60	21	15	43	57	90	86	28
250	250	22	24	49	38	66	110	70	25	15	44	65	90	109	28
300	300	26	30	58	58	94	148	82	25	18	56	75	90	134	28

Specification

- Plastic Duroplast (Phenolic PF)
 - reinforced
 - temperature resistant up to 110 °C
- **GN 520**
 - Hub bushing Steel, blackened
 - Threaded bushing Brass
 - Revolving handles GN 598 Plastic, Duroplast
 - Spindle Steel, zinc plated
- **GN 520.6**
 - Hub bushing Stainless Steel AISI 303
 - Threaded bushing Stainless Steel
 - Revolving handles GN 598.1 Plastic, Duroplast
 - Spindle Stainless Steel AISI 303
- RoHS compliant

Information

Disc handwheels GN 520 / GN 520.6 are renowned in particular for their design and the matt passivated aluminum ring in the front.

see also...

- Countersunk washers GN 184 / GN 184.5 (for axial fixing) → Page 542
- Keyway P9 DIN 6885 → Page 1124
- Cross holes GN 110 → Page 1127
- Strength properties → Page 1138

Disc handwheel, hub Steel

GN 520-125-K14-D

- 1 d₁
- 2 Bore code
- 3 d₂
- 4 Type

Disc handwheel, hub Stainless Steel

GN 520.6-150-B14-A

- 1 d₁
- 2 Bore code
- 3 d₂
- 4 Type