



elesa

ELESA Original design VDN.FP+IR



2 Bore code

- B** without keyway
- K** with keyway

4 Type

- D** with retractable handle

1 **3**

d ₁	d ₂ H7 Bore	d ₃	d ₄	d ₅	d ₆	d ₇	b	l ₁	l ₂	l ₃	l ₄	r	Ø Handle
100	10	24	22	35	54	39	26	12	33,5	51	56	37	22
125	12	32	26,5	44	70	46	28	15	38	57	56	48	22
150	14	32	26,5	50	80	48	30	15	38	60	65	57	23
175	16	40	33	55	90	56	32	15	43	66	80	68	26
200	20	40	33	55	90	60	32	15	43	68	90	76,5	28
225	20	49	40	66	110	66	33	15	44,5	71	90	88	28
250	22	49	40	66	110	70	36	15	44,5	75	90	100	28
300	26	58	58	94	148	82	36	18	56	87	90	124	28

Specification

- Plastic
Duroplast (Phenolic PF)
- reinforced
- temperature resistant up to 110 °C
- black, shiny finish
- Flash mark polished
- Hub bushing
Steel, blackened finish
- Retractable handles
- Plastic, Duroplast
black, shiny finish
- Retracting mechanism
Steel, blackened finish
- Keyway P9 DIN 6885 → Page 1124
- Cross hole GN 110 → Page 1127
- Strength properties → Page 1138
- Plastic characteristics → Page 1141
- RoHS compliant

On request

- without bore
- with safety-retractable handle
(swivelling back automatically)

Information

The handle in the handwheels GN 520.4 is locked in a conical bore in the operating position.

For reversal, it must first be pulled from the cone in axial direction.

A pressure spring holds the handle in both positions. When swung out, it automatically engages again.

This standard replaces the previous handwheels GN 520.3.

siehe auch...

- Countersunk washers GN 184 (for axial fixing) → Page 542
- Handwheels with retractable handle GN 521.3
(Plastic, bushing / Retracting mechanism Steel)
- Handwheels with retractable handle GN 524.3
(Plastic, bushing / Retracting mechanism Steel)

How to order

GN 520.4-200-K20-D

- 1** d₁
- 2** Bore code
- 3** d₂
- 4** Type