



ELESA Original design M.543 / M.543-p

l <sub>1</sub>	d	GN 528.1			GN 528.4		b	h	l <sub>2</sub>	l <sub>3</sub>	l <sub>4</sub>	s	t min.
		Material / Color		PP	Material / Color								
94 -1	M 6	SW	OR	-	-	-	21	36	107	79	-	6	10
105 ±0,5	M 5	SW	OR	-	-	-	23	37	120	90	-	7	10
105 ±0,5	M 6	SW	OR	-	-	-	23	37	120	90	-	7	10
117 ±0,5	M 6	SW	OR	SW	SW	OR	25	38	134	102	16	7,5	12
117 ±0,5	M 8	SW	OR	-	-	-	25	38	134	102	-	7,5	12
132 ±0,5	M 8	SW	OR	-	-	-	26	45	150	116	-	8	13
179 ±0,5	M 8	SW	OR	-	SW	OR	28	51	200	160	16	9	13
179 ±0,5	M 10	SW	OR	-	-	-	28	51	200	160	-	9	13

**Specification**

- Plastic **PA**  
Technopolymer (Polyamide)  
- glass fiber reinforced  
- temperature resistant up to 130 °C  
- black, RAL 9005, matte ● **SW**  
- orange, RAL 2004, matte ● **OR**
- Plastic **PP**  
Technopolymer (Polypropylene)  
- glass fiber reinforced  
- temperature resistant up to 100 °C  
- black, RAL 9005, matte ● **SW**
- Bushing  
Brass
- Threaded stud  
Steel, zinc plated
- Plastic characteristics → Page 1483
- Strength properties → Page 1448 / 1449
- RoHS compliant

**Information**

Cabinet „U“ handles GN 528.1 type PP (Polypropylene) offer indeed less mechanical and thermal features, however are of low cost. Their characteristics are sufficient for many applications.

see also...

- Cabinet „U“ handles GN 728  
(Aluminum, mounting from the back or the operator's side) → Page 92

How to order (with threaded bushing)		1	Material
		2	l <sub>1</sub>
GN 528.1 - PA - 132 - M8 - SW		3	d
		4	Color

How to order (with threaded stud)		1	Material
		2	l <sub>1</sub>
GN 528.4 - PA - 117 - M6 - SW		3	d
		4	Color

1.1  
1.2  
1.3  
1.4  
2.1  
2.2  
2.3  
2.4