



ROSTFREI
Inox
Stainless
Steel

1		2		3										
d ₁	d ₂	M 8	M 10	Length l			d ₃	d ₄	d ₅	h ₁	h ₂	h ₃	h ₄ Stroke	t min.
40	M 6	M 8	20	25	32	40	13,5	18	13,5	30	14	7	2,5	11
50	M 8	M 10	25	32	40	50	16	22	16,5	34	15	8	3,5	14

Specification

- Knob Plastic
Technopolymer (Polyamide PA)
- glass fiber reinforced
- temperature resistant up to 130 °C
- black, matt finish
- Threaded bushing / Threaded stud
- Steel **ST**
- blackened
- Stainless Steel AISI 303 **NI**
- Annular gear
Zinc die casting
- *Stainless Steel characteristics* → Page 1489
- *Plastic characteristics* → Page 1483
- **RoHS compliant**

On request

- caps in other colors
(standard color: black)

Information

Safety star knobs GN 5337.3 are most suitable for applications where an accidental or inconsiderate loosening or adjusting of the knob may lead to accidents.

In non-operative condition, the star knob is not linked with the threaded insert, i.e. the knob can be turned easily.

Only after axial pushing of the star knob, the two serrations get engaged so that the knob can be untightened resp. tightened.

After releasing, the two serrations are disengaged by a spring.

see also...

- *Safety tension levers GN 312* → Page 360 / 361

How to order (with threaded bushing)	1	d ₁
	2	d ₂
	4	Material

How to order (with threaded stud)	1	d ₁
	2	d ₂
	3	Length l
	4	Material