



elesa

ELESA Original design VC.692



Inox
Stainless
Steel

d₁	d₂	Length l								d₃	h₁	h₂ ≈
25	M 4	6	10	-	-	-	-	-	-	12	20	10
25	M 5	10	16	20	25	-	-	-	-	12	20	10
25	M 6	10	16	20	25	30	35	-	-	12	20	10
32	M 6	10	16	20	30	35	-	-	-	14	22,5	12,5
32	M 8	16	20	25	30	40	-	-	-	14	22,5	12,5
40	M 6	10	20	30	40	-	-	-	-	15	26	14
40	M 8	16	20	25	30	35	40	45	-	15	26	14
50	M 8	16	20	25	30	35	40	50	-	18	31	17
50	M 10	20	30	40	50	-	-	-	-	18	31	17
60	M 10	20	30	40	50	-	-	-	-	21	36,5	21
60	M 12	30	40	50	-	-	-	-	-	21	36,5	21

Specification

- Plastic
Technopolymer (Polyamide PA)
- glass fibre reinforced
- temperature resistant up to 130 °C
- black, matt finish
- Threaded stud
Stainless Steel AISI 303
- *Plastic characteristics → Page XYZ*
- *Stainless Steel characteristics → Page XYZ*
- **RoHS compliant**

On request

- Threaded stud
Steel zinc plated, blue passivated

Information

The underside of the knob GN 5337.4 is not recessed or hollowed. This means that if they are fitted with a Stainless Steel bush they will meet the standards and requirements for hygiene applications.

How to order

GN 5337.4-50-M10-30

- 1** d₁
- 2** d₂
- 3** Length l