



ELESA Original design VC.192 S-p-INOX



<b>d<sub>1</sub></b>	<b>d<sub>2</sub></b>	<b>Length l</b>					<b>d<sub>3</sub></b>	<b>h<sub>1</sub> +1</b>	<b>h<sub>2</sub> +1</b>
32	M 6	10	16	20	35	-	19	23	11
40	M 8	20	25	30	35	45	21	27	12
50	M 10	20	30	40	50	-	25	33	14
60	M 12	30	40	50	-	-	27	37	17

**Specification**

- Plastic Duroplast
  - temperature resistant up to 110° C
  - black, shiny finish
- Threaded bolt
  - Stainless Steel AISI 303
- *Stainless Steel characteristics* → Page 1144
- *Plastic characteristics* → Page 1141
- **RoHS compliant**

**Information**

Star knobs GN 5337.5 with threaded bolt meet highest quality requirements. Due to a special manufacturing process the mould parting line can be avoided.

Duroplast features very good chemical resistance.

The underside of the star knobs with threaded bolt have no recess and therefore meet more stringent hygiene requirements.

see also...

- *Star knobs with threaded bolt GN 5337.4 (Technopolymer)* → Page XYZ
- *Star knobs with threaded bolt GN 5337.2 (Technopolymer)* → Page XYZ
- *Star knobs GN 5337.5 (with threaded bush)* → Page XYZ

<b>How to order</b>	<b>1</b>	<b>d<sub>1</sub></b>
	<b>2</b>	<b>d<sub>2</sub></b>
	<b>3</b>	<b>Length l</b>
<b>GN 5337.5-40-M8-25</b>		