



ELESA Original design VC.192

**3 Type**

- S** with face and pointer
- Z** with pointer

<b>1</b> $d_1$		<b>2</b> $d_2$ H9 Bore		$d_3$	$d_4$	$d_5$	$d_6$	$d_7$	$e$	$h_1$	$h_2$	$h_3$	$h_4$	$h_5$	$l_1$	$l_2$
Type S	Type Z	Bore														
32	-	B	6	14	19	-	M 4	36	6	27	-	3	-	19	19	-
40	40	B	6	14	21	25	M 4	45	6	30	27	3	2	14	24	25
50	50	B	8	15	25	30	M 5	56	7	36	33	3	2	20	30	31
60	60	B	8	15	27	32	M 5	70	7	42	37	5	2	20	37	38
70	70	B	10	18	30	35	M 6	80	10	48	44	5	2	25	42	45

**Specification**

- Plastic
  - Knob: Duroplast (PF)
  - Pointer: Technopolymer (Polyamide PA)
  - temperature resistant up to 110 °C
  - black, shiny finish
- Bush
  - Brass: Size 32, 40
  - Steel: Size 50, 60, 70
- Arrow (Type S)
  - white
- Grub screw DIN 916
  - with internal hexagon and serrated point
- RoHS compliant

**Information**

Setting knobs GN 5338 are very appealing with a good gripping feel. The manufacturing technique has made it possible to produce them with no visible flash mark.

The hands are inserted into handle hub and **two** screws are used to hold them securely in position.

**How to order**

**GN5338-50-B8-S**

- 1**  $d_1$
- 2**  $d_2$
- 3** Type

1.1  
1.2  
1.3  
1.4  
1.5  
1.6  
1.7  
1.8  
1.9