



ELESA Original design MBT.p Color

d ₁		d ₂	Length l	d ₃	h ₁	h ₂					
Nominal dimension	Actual dimension										
32	31	M 5	10	20	40	-	-	-	15	24	11,5
32	31	M 6	10	16	20	25	30	40	15	24	11,5
40	39,5	M 6	10	16	20	30	40	-	17	26,5	12,5
40	39,5	M 8	16	20	25	30	40	50	17	26,5	12,5
50	50	M 8	16	30	50	-	-	-	20	33	16
50	50	M 10	20	30	50	-	-	-	20	33	16
60	61	M 10	20	30	50	-	-	-	23	39	18,5
60	61	M 12	20	30	50	-	-	-	23	39	18,5
70	70	M 12	30	50	-	-	-	-	24	42	20,5

Specification

- Plastic Technopolymer (Polypropylen PP) - reinforced, shock-resistant - temperature resistant up to 90 °C black, RAL 9005, matt ● **SW**

- Threaded stud Steel zinc plated, blue passivated

- Color of the cap (matt): black, RAL 9005 red, RAL 3000 ● **DRT**

• Plastic characteristics → Page 1483

• RoHS compliant

On request

- Cap in further colors

Information

The unique profile on the rim of the knurled screws GN 534 is characteristic of its form and the function.

see also...

- Knurled screws GN 7336 → Page 444
- Knurled screws GN 534 with loss protection GN 111.7 → Page 1426

How to order (with cap black)

1 2 3 4
GN 534-60-M12-30-SW

1	d ₁
2	d ₂
3	Length l
4	Color knob

How to order (with cap red)

1 2 3 4 5
GN 534-60-M12-30-SW-DRT

1	d ₁
2	d ₂
3	Length l
4	Color knob
5	Color cap

