



ELESA Original design MBT.p Color

1 $d_1$		2 $d_2$		3 Length l					$d_3$	$h_1$	$h_2$
Nominal dimension	Actual dimension										
32	31	M 5	10	20	40	-	-	-	15	24	11,5
32	31	M 6	10	16	20	25	30	40	15	24	11,5
40	39,5	M 6	10	16	20	30	40	-	17	26,5	12,5
40	39,5	M 8	16	20	25	30	40	50	17	26,5	12,5
50	50	M 8	16	30	50	-	-	-	20	33	16
50	50	M 10	20	30	50	-	-	-	20	33	16
60	61	M 10	20	30	50	-	-	-	23	39	18,5
60	61	M 12	20	30	50	-	-	-	23	39	18,5
70	70	M 12	30	50	-	-	-	-	24	42	20,5

**Specification**

- Plastic Technopolymer (Polypropylen PP) - reinforced, shock-resistant - temperature resistant up to 90 °C black, RAL 9005, matt ● **SW**

- Threaded stud Steel zinc plated, blue passivated

- Color of the cap (matt): black, RAL 9005 — red, RAL 3000 ● **DRT**

• Plastic characteristics → Page 1483

• RoHS compliant

**On request**

- Cap in further colors

**Information**

The unique profile on the rim of the knurled screws GN 534 is characteristic of its form and the function.

see also...

- Knurled screws GN 7336 → Page 444
- Knurled screws GN 534 with loss protection GN 111.7 → Page 1426

How to order (with cap black)

1  $d_1$   
2  $d_2$   
3 Length l  
4 Color knob  
**GN 534-60-M12-30-SW**

How to order (with cap red)

1  $d_1$   
2  $d_2$   
3 Length l  
4 Color knob  
5 Color cap  
**GN 534-60-M12-30-SW-DRT**

