


**2** Bore code

- B without keyway  
 K with keyway

**4** Type

- A without handle  
 D with revolving handle

**1**
**3**

d <sub>1</sub>	d <sub>2</sub> H7 Bore		d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	b	l <sub>1</sub> -0,5	l <sub>2</sub> -0,5	l <sub>3</sub> ≈	l <sub>4</sub> ≈	r	Ø Handle	No. of spokes
100	10	12	25	19	28	15	-	23	28	54,5	37	16	3
125	12	14	24	20	30	18	1	25	35	67	47	20	3
140	14	16	32	24	36	20	3	26	35	67	53	20	3
160	14	16	32	24	37	22	5	28	40	83	59	25	3
200	18	20	40	31	45	24	4	33	45	83	76	25	3
250	22	24	49	38	56	29	7	36	58	105,5	98	32	3
300	26	30	58	47	70	32	2	40	65	105,5	113	32	3

### Specification

- Plastic  
 Duroplast (Phenolic PF)  
 - reinforced  
 - temperature resistant up to 110 °C  
 - black, shiny finish  
 - Moulding flash removed and polished
- Hub bushing  
 Steel, blackened
- Threaded bushing  
 Brass
- Revolving handles DIN 98  
 Plastic, Technopolymer  
 black, matt
- Keyway P9 DIN 6885 → Page 1420
- ISO-Fundamental tolerances → Page 1479
- Plastic characteristics → Page 1483
- RoHS compliant

### Information

Face and bore are machined **after** the steel insert is pressed in, resulting in concentricity and squareness of rim.

They are also available without bore.

see also...

- Countersunk washers GN 184 (for axial fixing) → Page 814

#### How to order



- |   |                |
|---|----------------|
| 1 | d <sub>1</sub> |
| 2 | Bore code      |
| 3 | d <sub>2</sub> |
| 4 | Type           |