



- 2 Bore code**  
**B** without keyway  
**K** with keyway
- 4 Type**  
**A** without handle  
**D** with revolving handle

<b>1</b> $d_1$	<b>3</b> $d_2$ H7 Bore	$d_3$	$d_4$	$d_5$	$b$	$l_1 -0,5$	$l_2 -0,5$	$l_3 \approx$	$l_4 \approx$	$r$	$\emptyset$ Handle	No. of spokes	
100	10	12	25	19	28	15	-	23	28	54,5	37	16	3
125	12	14	24	20	30	18	1	25	35	67	47	20	3
140	14	16	32	24	36	20	3	26	35	67	53	20	3
160	14	16	32	24	37	22	5	28	40	83	59	25	3
200	18	20	40	31	45	24	4	33	45	83	76	25	3
250	22	24	49	38	56	29	7	36	58	105,5	98	32	3
300	26	30	58	47	70	32	2	40	65	105,5	113	32	3

**Specification**

- Plastic  
 Duroplast (Phenolic PF)  
 - reinforced  
 - temperature resistant up to 110 °C  
 - black, shiny finish  
 - Moulding flash removed and polished
- Hub bush  
 Steel, blackened
- Threaded bush  
 Brass
- Revolving handles DIN 98  
 Plastic, Technopolymer  
 black, matt
- Keyway P9 DIN 6885 → Page 1124
- ISO-Fundamental Tolerances → Page 1132
- Strength properties → Page 1138
- Plastic characteristics → Page 1141
- RoHS compliant

**Information**

Face and bore are machined **after** the steel insert is pressed in, resulting in concentricity and squareness of rim.

They are also available without bore.

see also...

- Countersunk washers GN 184 (for axial fixing) → Page 542

**How to order**

**GN 555-160-K16-D**

<b>1</b>	$d_1$
<b>2</b>	Bore code
<b>3</b>	$d_2$
<b>4</b>	Type

1.1  
1.2  
1.3  
1.4  
1.5  
1.6  
1.7  
1.8  
1.9