



ELESA Original design L.652 p

1

2

3

l ₁		d	l ₂			h ₁	h ₂	s
Nominal dimension	Actual dimension							Square
40	41	M 5	16	20	-	28	18,5	13
40	41	M 6	20	25	-	28	18,5	13
55	56,5	M 6	20	25	-	33	21,5	15
55	56,5	M 8	20	25	-	33	21,5	15
67	68,5	M 8	20	25	30	37	24,5	16,5
67	68,5	M 10	20	30	-	37	24,5	16,5
80	82	M 10	20	30	-	41,5	25	20
93	94	M 12	30	-	-	45	28,5	21

Specification

- Plastic
Technopolymer (Polyamide PA)
- glass fibre re-inforced
- temperature resistant up to 130 °C
- black, matt finish
- Threaded shaft Steel
zinc plated, blue passivated
- *Plastic characteristics* → Page 1141
- **RoHS compliant**

Information

GN 563.1 T-Handle screws can be used on operating levers as well as on clamping fixtures. These handles lend themselves ideally for very high manual clamping forces.

see also...

- *T-Handles GN 563.2 (Aluminium, with threaded bore)* → Page 44

How to order

GN 563.1-55-M8-20

1	l ₁
2	d
3	l ₂

1.1
1.2
1.3
1.4
1.5
1.6
1.7
1.8
1.9