



ELESA Original design MT-AT

1

2

| Length l | d <sub>1</sub> H9 Bore | d <sub>2</sub> | d <sub>3</sub> | d <sub>4</sub> | h <sub>1</sub> | h <sub>2</sub> | h <sub>3</sub> | h <sub>4</sub> ≈ | t min. | Ø Handle |
|----------|------------------------|----------------|----------------|----------------|----------------|----------------|----------------|------------------|--------|----------|
| 50       | B 6                    | 15             | 18             | 23             | 30             | 20,5           | 9              | 35               | 16     | 14       |
| 64       | B 8                    | 15             | 20             | 27             | 32             | 18,5           | 13,5           | 45               | 18     | 16       |
| 80       | B 10                   | 18             | 23,5           | 30             | 36             | 23,5           | 14             | 60               | 23     | 18       |
| 100      | B 12                   | 18             | 24             | 34             | 40             | 24,5           | 14,5           | 65               | 22     | 22       |
| 130      | B 14                   | 26             | 34             | 40             | 49             | 34             | 15,5           | 65               | 28     | 22       |
| 160      | B 16                   | 26             | 34             | 45             | 55             | 38             | 17,5           | 80               | 28     | 24       |

## Specification

- Body  
Plastic  
Technopolymer (Polyamide PA)
  - glass fiber reinforced
  - temperature resistant up to 90 °C
  - black, matte
- Hub bushing  
Steel, blackened
- Revolving handles
  - Plastic, Technopolymer  
black, matte
  - Spindle steel  
zinc plated, blue passivated
- Cross holes GN 110 → Page 1422
- ISO-Fundamental tolerances → Page 1479
- Plastic characteristics → Page 1483
- RoHS compliant

## Information

Cranked handles GN 570.2 are connected to a shaft by means of a cross pin.

How to order

GN 570.2-80-B10

1 Length l

2 d<sub>1</sub>