


ROSTFREI  
Inox  
Stainless  
Steel



Axial load-bearing capacity per eye nut



Load-bearing capacity at max. 45° per eye nut



Lateral load-bearing capacity at max. 45° per eye nut



Do not use under shear tension

**1**

d <sub>1</sub>			d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	e	h	k	m	F <sub>1</sub> max. in N	F <sub>2</sub> max. in N	F <sub>3</sub> max. in N
Steel ST	St. Steel NI	St. Steel A4										
M 8	M 8	-	20	36	20	8,5	36	8	10	1400	1000	700
M 10	M 10	M 10	25	45	25	10	45	10	12	2300	1700	1150
M 12	M 12	M 12	30	54	30	11	53	12	14	3400	2400	1700
M 16	M 16	M 16	35	63	35	13	62	14	16	7000	5000	3500
M 20	M 20	M 20	40	72	40	16	71	16	19	12000	8600	6000
M 24	M 24	M 24	50	90	50	20	90	20	24	18000	12900	9000
M 30	-	-	65	108	60	25	109	24	28	32000	23000	16000
M 36	-	-	75	126	70	30	128	28	32	46000	33000	23000

**Specification**

- Steel C 15 E **ST**
  - drop-forged
  - annealed
  - contact face machined
  - zinc plated, blue passivated
- Stainless Steel A2 **NI**
  - drop-forged
  - contact face machined
- Stainless Steel A4 **A4**
  - drop-forged
  - contact face machined
- Stainless Steel characteristics → Page 1489
- RoHS compliant

**2**

**Information**

The following guidelines of the lifting eye nuts DIN 582 have to be observed in addition to the load values given in the above table:

The eye nut must be of fully screwed in to achieve a perfect contact between the two mating faces.

Both threads must be of a equal length and the base material of equal strength to that of the nut.

Operating instructions with more details and specifications are included with every delivery (see also [www.ganter-griff.com/service](http://www.ganter-griff.com/service)).

The official DIN standard sheet specifies the additional sizes M42, M48, M56, M64, M72 x 6, M80 x 6 und M100 x 6.

see also...

- Lifting eye nuts (rotating) GN 583 → Page 1066
- Shackles GN 584 → Page 1076
- Shackles GN 585 → Page 1077

**How to order**

**DIN 582-M36-ST**

1 d<sub>1</sub>

2 Material

