



Type A

Type E



elesa

ELESA original design I.281/I.281+x-SST



4 Type

- A** with threaded bolt
- E** without threaded bolt

2	3	3	3	3	3	3	3	3	3	3	3	3
d ₁	d ₂ 6g Type A	-	d ₃ ^{+0.3 +0.1} Type E	d ₄	d ₅	l ₁	l ₂	l ₃	l ₄	l ₅	A/F	
18	M 6	-	8	15	12	40	13	0,3	39	35	4	
21	M 8	-	10	17	14	50	15	0,5	49	43	5	
23	M 8	M 10	12	19	16	65	17	0,5	64	56	6	
26	M 10	-	13	21	17	80	18	0,5	79	70	6	
28	M 10	-	14	22	19	90	18	0,5	89	79	8	
31	M 12	-	16	25	20	102	20	1	100	89	8	

Specification

- Plastic
Duroplast (Phenolic PF)
- temperature resistant up to 110 °C
- black, shiny finish

- Threaded bolt
Stainless Steel AISI 304

• *Plastic characteristics* → Page 1483

• *Stainless Steel characteristics* → Page 1489

• **RoHS compliant**



KU

Information

The outstanding feature of revolving handles GN 598.2 is their highly robust design. Type E is suitable for use in connection with user-specific threaded bolts.

How to order (with threaded bolt)

1 **2** **3** **4**
GN 598.2-KU-31-M12-A

1 Material

2 d₁

3 d₂

4 Type

How to order (without threaded bolt)

1 **2** **3** **4**
GN 598.2-KU-26-13-E

1 Material

2 d₁

3 d₃

4 Type