



ELESA Original design: ERX.p



1		2		3																	
l ₁	d ₁	l ₂										d ₂	d ₃	h ₁	h ₂	h ₃	h ₄	Stroke			
30	M 5	-	-	10	16	20	-	-	-	-	-	-	-	-	12	15,5	29,5	6	30	3,5	
30	M 6	-	-	10	16	20	25	30	40	-	-	-	-	-	12	15,5	29,5	6	30	3,5	
44	M 5	-	-	10	16	20	-	-	-	-	-	-	-	-	12	15,5	29,5	6	32,5	3,5	
44	M 6	-	-	10	16	20	25	30	40	45	-	-	-	-	12	15,5	29,5	6	32,5	3,5	
63	M 6	-	-	10	16	20	25	30	35	40	50	-	-	-	15	19	37,5	8	43	4	
63	M 8	-	-	16	20	25	30	35	40	45	50	60	70	15	19	37,5	8	43	4		
63	M 10	-	-	20	40	50	60	-	-	-	-	-	-	15	19	37,5	8	43	4		
78	M 8	-	-	20	25	30	40	45	50	55	60	70	-	19	24,5	47	12	54	4		
78	M 10	-	-	20	25	30	35	40	50	60	70	-	-	19	24,5	47	12	54	4		
78	M 12	-	-	20	25	30	35	40	45	50	60	70	80	19	24,5	47	12	54	4		
95	M 12	M 16	-	30	50	70	-	-	-	-	-	-	-	21,5	26,5	54,5	13	64,5	4,5		
108	M 12	M 14	M 16	30	50	70	-	-	-	-	-	-	-	25	30	54,5	11	65,5	4,5		

* not available from stock, requires a minimum order quantity

Specification

- Handle
Plastic
Technopolymer (Polyamide PA)
- glass fibre reinforced
- temperature resistant up to 130 °C
- black-grey, similar RAL 7021
- Color of the releasing button:
black-grey, RAL 7021
orange, RAL 2004
grey*, RAL 7035
yellow*, RAL 1021
blue*, RAL 5024
red*, RAL 3000
- Threaded stud
Steel zinc plated, blue passivated
- Plastic characteristics → Page 1483
- RoHS compliant

- **DSG**
- **DOR**
- **DGR**
- **DGB**
- **DBL**
- **DRT**

Information

Adjustable hand levers GN 603, like all the products of the Ergostyle® range, are renowned for their good style but also their ergonomic shape.

They are like all adjustable hand levers ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

The releasing button offers an easy disengagement. Its use is limited to applications where dismantling of the lever for installation is not required.

see also...

- Product family Ergostyle® → Page 17
- Adjustable hand levers GN 603.1 (with releasing button, threaded stud Stainless Steel) → Page 345

How to order	1	l ₁
	2	d ₁
	3	l ₂
GN 603-63-M8-20-DOR	4	Color of the releasing button