



ELESA Original design IZP.

**3 Type**

- N** neutral  
**M** with arrow  
**S** with scale 0...9  
 20 graduations

**1****2**

<b>d<sub>1</sub></b> 17	<b>d<sub>2</sub></b> H8 Bore	<b>d<sub>3</sub></b>	<b>d<sub>4</sub></b>	<b>d<sub>5</sub></b>	<b>d<sub>6</sub></b>	<b>l<sub>1</sub></b>	<b>l<sub>2</sub></b>	<b>l<sub>3</sub></b>	<b>t<sub>1</sub></b>	<b>t<sub>2</sub></b>
27	B 6	22	25	20,5	M 4	30	12	18	24	12
32	B 8	25	30	25	M 4	38	13	23	30	13
35	B 10	28	33	26,5	M 5	45	15	27	37	15
40	B 12	33	38	31	M 5	52	16,5	32	44	16

**Specification**

- Plastic Technopolymer (Polyamide PA)
  - glass fiber reinforced
  - temperature resistant up to 130 °C
  - black, shiny finish
- Arrow (Type M) and scale (Type S) white, engraved with laser precision
- Grub screw DIN 916 with internal hexagon and serrated point
- ISO-Fundamental tolerances → Page 1479
- Plastic characteristics → Page 1483
- RoHS compliant

**On request**

- special graduations see „How to order Graduations“ → Page 252

**Information**

Besides the standard scale (Type S) the scale knobs GN 626 can be supplied with any type of graduation.

Regarding design, numbering run, numbering position and numbering sequence of the scale please see the layout for scale knobs on the order sheet „How to order Graduations“ → Page 252

see also...

- Control knobs GN 526 (Plastic) → Page 257
- Control knobs GN 726 / GN 726.1 (Aluminum) → Page 259
- Clamping elements GN 826 (for adjustable spindles) → Page 268

How to order

GN 626-40-B12-N

<b>1</b>	<b>d<sub>1</sub></b>
<b>2</b>	<b>d<sub>2</sub></b>
<b>3</b>	<b>Type</b>