



ELESA Original design IZP.

- 3 Type**
- N** neutral
  - M** with arrow
  - S** with scale 0...9  
20 graduations

1

2

d <sub>1</sub> f7	d <sub>2</sub> H8 Bore	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	t <sub>1</sub>	t <sub>2</sub>
27	B 6	22	25	20,5	M 4	30	12	18	24	12
32	B 8	25	30	25	M 4	38	13	23	30	13
35	B 10	28	33	26,5	M 5	45	15	27	37	15
40	B 12	33	38	31	M 5	52	16,5	32	44	16

**Specification**

- Plastic  
Technopolymer (Polyamide PA)  
- glass fibre reinforced  
- temperature resistant up to 130 °C  
- black, shiny finish
- Arrow (Type M) and scale (Type S)  
white, engraved with laser precision
- Grub screw DIN 916  
with internal hexagon and serrated point
- ISO-Fundamental Tolerances → Page xx
- Plastic characteristics → Page xx
- RoHS compliant

**Information**

Besides the standard scale (Type S) the scale knobs GN 626 can be supplied with any type of graduation.  
Regarding design, numbering run, numbering position and numbering sequence of the scale please see the layout for scale knobs on the order sheet „How to order Graduations“ → Page xx

see also...

- Control knobs GN 526 (Plastic) → Page xx
- Control knobs GN 726 / GN 726.1 (Aluminium) → Page xx
- Clamping elements GN 826 (for adjustable spindles) → Page xx

**On request**

- special graduations  
see „How to order Graduations“ → Page xx

How to order

GN626-40-B12-N

1	d <sub>1</sub>
2	d <sub>2</sub>
3	Type