



elesa

ELESA Original design EBP/DS-EBP.



3 Type

- A Mounting from the back (threaded blind bore)
- B Mounting from the operator's side

Distance bushing GN 628.2

l ₁	d ₁ Form A	d ₂ Form B	d ₃	d ₄	d ₅	d ₆	h ₁	h ₂	h ₃	l ₂	l ₃ min.	s	t ₁	t ₂
94 -1	M 5	-	22	-	22,5	6,5	35	-	18	116	71	7,5	10	-
94 -1	M 6	6,5	22	13,5	22,5	6,5	35	17	18	116	71	7,5	12	6,5
117 ±0,5	M 6	6,5	26	17	26,5	6,5	39	7	19,5	144	91	8,5	13	19,5
117 ±0,5	M 8	8,5	26	17	26,5	8,5	39	18	19,5	144	91	8,5	13	8,5
132 ±0,5	M 6	-	27	-	-	-	42	-	-	159	105	9,5	13	-
132 ±0,5	M 8	8,5	27	-	-	-	42	17,5	-	159	105	9,5	13	10,5
150 ±1	M 8	8,5	28	18	29	9	45	18	20,5	180	122	9,5	13	14
179 ±1	M 8	8,5	29	18	29	9	51	19	20,5	210	150	9,5	13	16
179 ±1	M 10	-	29	-	-	-	51	-	-	210	150	9,5	13	-

Specification

- Plastic Technopolymer (Polyamide PA)
 - glass fiber reinforced
 - temperature resistant up to 130 °C
 - black-gray, matte similar RAL 7021

- Bushing (Type A) Brass

- Color of the cover cap (matte):
 - black-gray, RAL 7021
 - orange, RAL 2004
 - gray, RAL 7035
 - yellow, RAL 1021
 - blue, RAL 5024
 - red, RAL 3000

- DSG
- DOR
- DGR
- DGB
- DBL
- DRT

- Plastic characteristics → Page 1483
- Strength properties → Page 1449
- RoHS compliant

Information

The design of the GN 628 cabinet „U“ handles matches the Ergostyle® product family.

The cover caps for type A are supplied ready assembled, for type B they are enclosed loose.

The „hand space“ can be enlarged with the GN 628.2 distance bushings.

see also...

- Product family Ergostyle® → Page 17
- Assembly sets for profile systems 30 / 40 GN 965 → Page 1428
- Assembly sets for profile systems 30 / 40 / 45 GN 968 → Page 1438

How to order	1	l ₁
	2	d ₁ (d ₂)
	3	Type
	4	Color of the cover cap

How to order (Distance bushing)	5	h ₃
GN 628.2-20,5		